



**FMS-1/350-P**  
BULK FUEL FILTER

**FMS-C70-BPE**  
COALESCING FUEL FILTER

100% SYNTHETIC MEDIA

# ULTRA CLEAN AND DRY DELIVERY

## FMS-1/350-P



**RETENTION  
OF PARTICLES**

### ELEMENT TECHNICAL SPECIFICATIONS FMS-1/350-P

Efficiency	Beta 4-4193 (ISO 16889:99)
DHC	3000 grams (MTD)
Maximum Pressure	150 psi
Recommended Flow	350 gpm
Dimensions	42x6.25x6.25"
Weight	21 lbs
Housings	FMS-350-BP

### THETA 4>43 10 SINGLE PASS TEST

	ISO CODES	PARTICLES		
		4 µm	6 µm	14 µm
Reservoir Contaminant Level	22/21/18	31898	14071	542
Average Cleanliness at Downstream	10/8/6	7.4	1.7	0.34




## FMS-C70-BPE

**WATER / EMULSIONS  
COALESCENCE REMOVAL**



### ELEMENT TECHNICAL SPECIFICATIONS FMS-C70-BPE

Efficiency	98.6% SAE J1488 Certified
DHC	Drain
Maximum Flow	80 gpm
Recommended Flow	70 gpm
Dimensions	40x6x6"
Weight	18 lbs
Housings	FMS-C70-BP



Contamination control at dispatch is a fundamental part of best practice. Our bottom-connected lockbox filters are the only ones that can be installed on the ridge of subway tanks and handle multiple dispensing guns.

Water and emulsions cause up to 15% of power loss, thus up to 15% increase in fuel consumption. All ISO 4406 contamination control plans must contemplate water and emulsions with SAE J1488 certified systems.



SCAN TO VISIT OUR WEBSITE



FMS INTERNATIONAL INC.

580 W Park Rd Leetsdale,  
PA 15056  
USA

+1 724 340 4210  
info@fms-filtration.com  
fms-filtration.com